

液压摆式剪板机
HYDRAULIC SWING BEAM SHEAR



产品介绍 / Product Introduction

1. 摆式上刀架、液压传动，剪切稳定可靠，操作方便。
 2. 刃口间隙调整准确迅速；上刀架行程可无级调节，提高剪切速度。
 3. 可选配多种数控系统控制后挡料及刃口间隙等。
1. Swing beam type top blade, hydraulic driven, stable and reliable, easy to operate;
 2. blade gap can be adjusted accurately and rapidly; top blade stroke can be adjusted stepless to improve cutting speed.
 3. Matching variety of back gauges and blade gaps which controlled by CNC system.



气动托料
Pneumatic back material holder



后护栏
Back protective fence

型号 Model	可前规格 Shear Size(T × W) (mm)	剪切角度 Shear Angle	压脚数量 Clamps	行程次数 Strokes (min-1)	后挡料 Back Gauge Range(mm)	主电机 Main Motor (KW)	油箱容积 Volume of oil tank (L)	重量 Weight (kg)	单机外形尺寸 Overall Dimensions (L × W × H)(mm)
QC12Y-4×2000	4×2000	1°30'	10	20	20-600	7.5	220	3800	2590×1610×1715
QC12Y-4×2500	4×2500	1°30'	13	20	20-600	7.5	247	4295	3140×1610×1630
QC12Y-4×4000	4×4000	1°30'	18	8	20-600	7.5	247	7550	4640×1610×1830
QC12Y-6×2000	6×2000	1°30'	10	20	20-600	7.5	220	4600	2590×1610×1720
QC12Y-6×2500	6×2500	1°30'	13	18	20-600	7.5	247	5250	3140×1610×1630
QC12Y-6×3200	6×3200	1°30'	14	14	20-600	7.5	247	6260	3840×1610×1630
QC12Y-6×4000	6×4000	1°30'	18	12	20-600	11	315	8900	4660×1670×1830
QC12Y-6×5000	6×5000	1°30'	22	7	20-800	11	587	15800	5770×2152×2065
QC12Y-6×6000	6×6000	1°30'	25	7	20-800	15	689	22200	6800×2300×2360
QC12Y-8×2500	8×2500	1°30'	13	14	20-800	11	247	5300	3140×1610×1660
QC12Y-8×3200	8×3200	1°30'	14	10	20-600	11	247	6300	3840×1610×1660
QC12Y-8×4000	8×4000	1°30'	18	8	20-600	11	247	9150	4700×1690×1830
QC12Y-8×5000	8×5000	1°30'	22	7	20-800	15	587	18500	5860×2252×2215
QC12Y-8×6000	8×6000	1°30'	25	6	20-800	15	689	24600	6870×2468×2410
QC12Y-10×2500	10×2500	2°	12	10	20-600	15	247	7750	3400×1690×1800
QC12Y-10×3200	10×3200	1°48'	13	8	20-600	15	247	9150	4100×1690×1900
QC12Y-10×4000	10×4000	1°54'	15	12	20-800	18.5	570	14700	4850×2152×2090
QC12Y-12×2500	12×2500	2°	12	10	20-600	15	247	7750	3400×1690×1800
QC12Y-12×3200	12×3200	1°30'	14	10	20-800	18.5	570	12000	4085×2050×2120
QC12Y-12×4000	12×4000	2°	15	8	20-800	18.5	570	15350	4870×2250×2150
QC12Y-12×5000	12×5000	2°	21	8	20-800	30	780	22350	5900×2480×2400
QC12Y-16×2500	16×2500	2°	12	8	20-800	18.5	390	11500	3435×2050×2130
QC12Y-16×3200	16×3200	2°	14	7	20-800	18.5	570	14500	4120×2192×2155
QC12Y-16×4000	16×4000	2°	15	7	25-800	30	715	20000	4900×2300×2315
QC12Y-20×2500	20×2500	2°30'	12	6	20-800	37	746	15000	3450×2075×2515
QC12Y-20×3200	20×3200	2°30'	15	5	25-800	37	930	19000	4180×2300×2600
QC12Y-20×4000	20×4000	2°30'	12	5	30-1000	37	1324	24000	4950×2388×2760
QC12Y-25×2500	25×2500	3°	12	5	40-800	45	840	16750	3460×2300×2696

本参数若有变更，恕不另行通知。
Due to continual improvements, specifications are subject to change without notice.